

VL-VQ7000SX

SIP Based Guard Station

Guard Station

- SIP Based Guard Station
- 7-inch TN LCD with capacitive Touch Screen
- Build-In Handset Microphone and Receiver Speaker
- Supports Emergency calls
- 3rd Party SIP device compatibility (SIP/Alarm/RTSP)
- Real-time Alarm Information from site/building
- POE 802.3af

ENQUIRE NOW


20:00
04 / August / 2025, Monday
Call
Monitor
Alarm
Record
Message
Setting
Panasonic

Category	Component	Specification
System parameters	Operation System	Android 12
Display parameters	Display Type	7-inch Colour TN LCD
	Operation Method	Capacitive touch screen
	Resolution	1024 x 600 pixels
Video parameters	Video Codec	H.264
	Video Resolution	Main stream: FHD 1920 x 1080 (Optional: HD 720P , VGA)
	Image Sensor	-
	View Angle	-
	Lighting Method	-
	Minimum Illuminance	-
Audio parameters	Audio Codec	G.711
	Audio Output	Built-in monitor loudspeaker and handset receiver speaker
	Audio Input	Built-in handset microphone
	Audio Quality	Noise suppression and echo cancellation
	DTMF unlock	-

Category	Component	Specification
Network Parameters	Wireless network	-
	Wiring	UTP (Cat 5e or higher)
	Network Protocol	TCP/IP, SIP2.0, RTSP
Interface	Network Interface	1(RJ45, 10BASE-T/100BASE-TX (Auto MDI/MDI-X))
	Power Output	-
	12V DC input	1
	Relay Lock	-
	Wiegand	-
	Door Station Port	-
	4-wire input	-
	Alarm In	-
	Alarm Out (Power Output)	-
	Micro SD Card	-
	Speaker volume knob	-
	CAM standard switch	-
	Exit button	-
Unlock way	Unlock way	-
	Face Recognition Capacity	-
	RFID (Capacity)	-
	RFID to unlock	-
Capacity	Linked IP Camera	Yes (Up to 32)
	Text Messages	Y (up to 100)
	Voice Messages	N

Category	Component	Specification
	Intercom Logs	Y (up to 100)
	Alarm Logs	Y (up to 500)
	Recording	Y (100 pcs for picture recording)
General	Power Source	PoE (IEEE 802.3af compliant, Class 0 device) / DC adaptor
	Operating Voltage	48V POE / 12V DC
	Current Rating	POE 48V, 0.16A / DC 12V, 0.64A
	Power Consumption	Standby: 2.5 W, Maximum: 7.7 W
	Installation	Desktop
	Colour	Black
	Dimensions (mm) (H x W x D)	30 x 312 x 168
	Working Temperature	115 x 312 x 185 with handset and desk bracket
	Storage Temperature	-10 ℃ to +55 ℃(14 ℉ to 131 ℉)
	Relative Humidity	-20 ℃ to +60 ℃(-4 ℉ to 140 ℉)
	Ingress Protection	10% to 90% RH
	Inverse Kinematics	-
	Display Language	-
	Tamper alarm	English
	Motion Detect	-
	Face liveliness check	-
	External Material	Aluminum alloy
	Weight	1.7 kg

Panasonic

Follow Us

Products

Surveillance Camera

Network Video Recorder

Security Solutions

Other Links

About Us

Case Studies

News & Blogs

Contact Us

Panasonic Life Solutions India Pvt. Ltd.
Intellion Park, 12th Floor, Tower 3, Sector 59, Golf Course Extension Road,
Gurugram – 122011, Haryana, India

Email Address:
sales.ccve@in.panasonic.com

Privacy Policy

Products exclusively imported and marketed by Panasonic Life Solutions India Pvt. Ltd.

Terms of Use