

VL-VQ9000SX

Lobby Display Station

Lobby Display Station with 7" Screen for IP SIP VDP

- 7-inch IPS LCD with Touch Panel
- Dual 2MP Camera for High-Definition Video & Images
- Multiple Access Control – Face, IC cards, QR Code, Password, Smartphone
- Face Recognition (up to 10,000)
- Night Vision with Automatic LED Lights
- Aluminum Housing with IP65& IK07 rating
- Supports 2 NO/NC Locks,3 Exit buttons
- 3rd Party SIP device compatibility


Panasonic

COMPONENT	SPECIFICATION	Value
System parameters	Operation System	Android 12
Display parameters	Display Type	7-inch Colour IPS LCD
	Operation Method	Touch panel
	Resolution	1024 x 600 pixels
Video parameters	Video Codec	H.264
	Video Resolution	Main stream: FHD 1920 x 1080 (Optional: HD 720P , VGA)
	Image Sensor	CMOS 2MP (1920 x 1080)
	View Angle	H: 112, V: 60, D:130
	Lighting Method	White coloured LED light, IR LED
	Minimum Illuminance	0.01lx (within approx. 50cm from the camera)
Audio parameters	Audio Codec	G.711
	Audio Output	Built-in loudspeaker
	Audio Input	Built-in omnidirectional microphone
	Audio Quality	Noise suppression and echo cancellation
	DTMF unlock	Support

Network Parameters	~~Wireless network~~	
	Wiring	UTP (Cat 5e or higher)
	Network Protocol	TCP/IP, SIP2.0, RTSP
Interface	Network Interface	1(RJ45, 10BASE-T/100BASE-TX (Auto MDI/MDI-X))
	Power Output	1 (12 V / 150 mA output) for lock devices
	12V DC input	1
		-
	Relay Lock	2
	Wiegand	1 input and 1 output, 12V/150mA output
	Door Station Port	-
	4-wire input	-
	Alarm In	-
	Alarm Out (Power	-
	Output)	1 (8-32 GB)
	Micro SD Card	-
	Speaker volume knob	-
	CAM standard switch	3
	Exit button	Y (Face Recognition / QR code / RFID / Password / Remote unlock with
	Unlock way	Smartphone/ DTMF)
	Face Recognition	Y (10000 pcs)
	Capacity	Y (10000 pcs)
	RFID (Capacity)	ISO/IEC 14443 Type A (MIFARE)(Frequency: 13.56 MHz) (Transmission power:
	RFID to unlock	-3.354 dBμA/m(max)@3m)

	~~Linked IP Camera~~	
Capacity	Text Messages	-
	Voice Messages	-
	Intercom Logs	-
	Alarm Logs	-
	Recording	-
General	Power Source	PoE (IEEE 802.3af compliant, Class 0 device) / DC adaptor
	Operating Voltage	48V POE / 12V DC
	Current Rating	POE 48V, 0.26A / DC 12V, 0.96A
	Power Consumption	Standby: 8.0 W, Maximum: 12.5 W
	Installation	Flush mounted, embedding box available
	Colour	Black
	Dimensions (mm) (H x W x D)	355 x 160 x 58
	Working Temperature	-10 °C to +55 °C(14 °F to 131 °F)
	Storage Temperature	-20 °C to +60 °C(-4 °F to 140 °F)
	Relative Humidity	10% to 90% RH
	Ingress Protection	IP65
	Inverse Kinematics	IK07
	Display Language	English
	Tamper alarm	Support
	Motion Detect	-
	Face liveliness check	Liveliness level sensitivity adjustable
	External Material	Aluminum alloy
	Weight	1.5 kg

Panasonic

Follow Us

Surveillance Camera

Network Video Recorder

Security Solutions

About Us

Case Studies

News & Blogs

Panasonic Life Solutions India Pvt. Ltd.
Intellion Park, 12th Floor, Tower 3, Sector 59, Golf Course Extension Road,
Gurugram – 122011, Haryana, India

Email Address:
sales.ccve@in.panasonic.com

Privacy Policy

Products exclusively imported and marketed by Panasonic Life Solutions India Pvt. Ltd.

Terms of Use