

VL-VQ1000SX

Single button Video Door Station

Door Station

- Single button Video Door Station
- 2MP FHD Camera with 120 degree angle
- Noise Suppression and Echo cancellation feature
- Door Lock Release Port
- Night Vision with white LED Lights
- Aluminum Housing with IP65 & IK07 rating

ENQUIRE NOW


Panasonic

System Parameters

COMPONENT	SPECIFICATION
Operation System	-

Display parameters

COMPONENT	SPECIFICATION
Display Type	-
Operation Method	-
Resolution	-

Video Parameters

COMPONENT	SPECIFICATION
Video Codec	-

Video Resolution	Main
Image Sensor	CMOS 2MP (1920 x 1080)
View Angle	H120, V62, D145
Lighting Method	White coloured LED light
Minimum Illuminance	0.01lx (within approx. 50cm from the camera)

Audio Parameters

COMPONENT	SPECIFICATION
Audio Codec	G.711
Audio Output	Built-in loudspeaker
Audio Input	Built-in omnidirectional microphone
Audio Quality	Noise suppression and echo cancellation
DTMF unlock	-

Wireless network	-
Wiring	-
Network Protocol	-

Interface

COMPONENT	SPECIFICATION
Network Interface	-
Power Output	-
12V DC input	-
Relay Lock	1
Wiegand	-
Door Station Port	-

4 wire input	1
Alarm In	-
Alarm Out (Power Output)	-
Micro SD Card	-
Speaker volume knob	1
CAM standard switch	1 (Support AHD and CVBS switching)
Exit button	-

Unlock way

COMPONENT	SPECIFICATION
Network Unlock way	-
Face Recognition Capacity	-
RFID (Capacity)	-

RFID to unlock

Capacity

COMPONENT	SPECIFICATION
Linked IP Camera	-
Text Messages	-
Voice Messages	-
Intercom Logs	-
Alarm Logs	-
Recording	-

General

COMPONENT	SPECIFICATION
Power Source	Powered by monitor

Operating Voltage	
Current Rating	DC 14.5V, 0.29 A
Power Consumption	Standby: 0 W, Maximum: 4.3 W
Installation	Surface mounted, corner bracket available
Colour	Black
Dimensions (mm) (H x W x D)	133 x 48 x 21
Working Temperature	-10 °C to +55 °C(14 °F to 131 °F)
Storage Temperature	-20 °C to +60 °C(-4 °F to 140 °F)
Relative Humidity	10% to 90% RH
Ingress Protection	IP65
Inverse Kinematics	IK07
Display Language	-

Tamper alarm	
Motion Detect	Support
Face liveliness check	-
External Material	Metal
Weight	190 g