







VL-SA71

Basic Analog Video Door Phone Kit

Basic Analog Video Door Phone Kit

ENQUIRE NOW


Panasonic
VL-VA501SX
TALK
Panasonic
VL-MA71SX

Model number and name	VL-MA71 Main Monitor Station (Main monitor) Extension Monitor	VL-VA502 Door Station (Doorphone)
Power source	DC 14.5V 1A, 50/60 Hz	Power supplied by the main monitor
Power consumption	Standby: <3.0 W, Operating: <10.0 W	-
Dimensions (H x W x D) (Excluding protruding sections)	140 x 190 x 22 mm	150 x 95 x 41 mm
Weight	320 g	228 g
Operating environment	Ambient temperature: Approx. -20 °C to +70 °C Relative humidity (non-condensing): 10 % to 90 %	Ambient temperature: Approx. -20 °C to +70 °C Relative humidity (non-condensing): 10 % to 90 %
Display	7-inch wide colour capacitive touchscreen (Approx. 17.8cm)	-
Monitor Resolution	1024 x 600	-
Display language	English, Arabic	-

Talking method	Hands-free	-
Viewing angle	-	Diagonally: Approx. 120˚ Horizontally: Approx. 90˚ Vertically: Approx. 66˚
Internal Memory	NA	-
External Memory	NA	-
Camera Resolution	-	1/3" CMOS with 2MP Lens
Installation method	Wall mount (mounting bracket supplied)	Surface mount (mounting base supplied)
Lock Connection Relay	-	1 Relay (No Com NC)
Minimum illuminance required	-	1 lx (within approx. 50 cm from the camera lens)
Lighting method	-	White LED
IP rating / IK rating	-	IP65 / IK08

Panasonic

Follow Us

Products

Surveillance Camera

Network Video Recorder

Security Solutions

Other Links

About Us

Case Studies

News & Blogs

Contact Us

Panasonic Life Solutions India Pvt. Ltd.
Intellion Park, 12th Floor, Tower 3, Sector 59, Golf Course Extension Road,
Gurugram – 122011, Haryana, India

Email Address:
sales.ccve@in.panasonic.com

Privacy Policy

Products exclusively imported and marketed by Panasonic Life Solutions India Pvt. Ltd.

Terms of Use