







VL-SA611

Hybrid Video Door Phone Kit with Mobile App Access

Hybrid Video Door Phone Kit with Mobile App Access

ENQUIRE NOW


Panasonic
VL-VA511SX

Model number and name	VL-MA611 Main Monitor Station (Main monitor) Extension Monitor	VL-VA511 Door Station (Doorphone)
Power source	DC 14.5V 1A, 50/60 Hz	Power supplied by the main monitor
Power consumption	Standby: <3.0 W, Operating: <10.0 W	-
Dimensions (H x W x D) (Excluding protruding sections)	143 x 200 x 22 mm	150 x 95 x 41 mm
Weight	408 g	226 g
Operating environment	Ambient temperature: Approx. -20 °C to +70 °C Relative humidity (non-condensing): 10 % to 90 %	Ambient temperature: Approx. -20 °C to +70 °C Relative humidity (non-condensing): 10 % to 90 %
Display	7-inch wide colour capacitive touchscreen (Approx. 17.8cm)	-
Monitor Resolution	1024 x 600	-
Operating System	Linux	-

Wi-Fi Connectivity	2.4 G Hz Only	-
Mobile App Supported	Panasonic SmartWiFi	-
Display language	English, Arabic	-
Talking method	Hands-free	-
Viewing angle	-	Diagonally: Approx. 155˚ Horizontally: Approx. 120˚ Vertically: Approx. 60˚
Internal Memory	100 Images	-
External Memory	Max 256 GB SD Card Supported (Class 10 & Above)	-
Camera Resolution	-	1/2.9" CMOS with 2MP Lens
Stream Resolution (video)	1280 x 720 pixels	-
Stream Resolution (image)	1024 x 600 pixels	-

Installation method	Wall mount (mounting bracket supplied)	Surface mount (mounting base supplied)
Lock Connection Relay	1 Relay (No Com NC)	1 Relay (No Com NC)
Minimum illuminance required	-	1 lx (within approx. 50 cm from the camera lens)
Lighting method	-	White LED
IP rating / IK rating	-	IP65 / IK08