







VL-SA74

IP Video Door Phone Kit

ENQUIRE NOW



Model Number & Model Name	VL-VC3900BX-E Lobby Station

Model number and name	**VL-VA514 4-Button Door Station** (Doorphone)
Power source	DC 14.5V 1A, 50/60 Hz
Power consumption	Standby: <3.0 W, Operating: <10.0 W
Dimensions (H x W x D)	(Excluding protruding sections) 143 x 200 x 22 mm
Weight	351 g
Operating environment	Ambient temperature: Approx. -20 °C to +70 °C Relative humidity (non-condensing): 10 % to 90 %
Tamper Support	Yes
Supported Models	Supports Monitors from models: VL-SA71SX, VL-SA72SX & VL-SA611SX* (* Use Toggle switch to choose AHD or Analog Monitor)

Support	Toggle Switch button for choosing AHD and Analog model monitor
Talking method	Hands-free
Audio Quality	Noise Suppression, Echo Cancellation
Audio Input	Built-in Omnidirectional Microphone
Viewing Angle	Diagonally: Approx. 155˚ Horizontally: Approx. 120˚ Vertically: Approx. 60˚
Camera Resolution	1/3" CMOS with 2MP Lens
Stream Resolution (video)	CVBS : 720 X 576 / AHD : 1024 X 600
Stream Resolution (image)	CVBS : 720 X 288 / AHD : 1024 X 600
Installation method	Surface Mount / Flush Mount
Lock Connection Relay	1 Relay (No Com NC)
Minimum illuminance required	1 lx (within approx. 50 cm from the camera lens)

Lighting method	White LED
IP rating / IK rating	IP65 / IK10