

4MP Smart Dual Lens 4G Mini PTZ Camera



FEATURES

- 4MP Smart Dual Lens 4G Pan/Tilt Camera
- Dual Intelligent Lens 2.8 mm & 12 mm
- Horizontal & Vertical Viewing; Pan 350°, Tilt 90°
- Unique With All-Time-Color vision
- Built-in active Defence Strobe Light & Siren
- Intelligent motion tracking, automatically tracking when people break area
- Built-in high-sensitivity Mic and Speaker, Half Duplex Audio Intercomm
- Area motion detection, Humanoid detection, Push Ralttime Notification on the Application
- Custome Voice Recordable massage for Audio Alerts Boardcast
- Can be set 6 preset points favorite locations
- 10X Combined Zoom
- Alexa Support
- Support monitoring: Pc/Mobile on Truecloud
- Compression: H.264/H.265/H.265+



4G SIM Support



256GB SD Card



4MP Resolution



Works with Alexa



Auto Human Tracking



H.265+ Compression



All Time Colour



10X Zoom



Cloud Recording



Location Presets

Technical Specifications

Product code	T18155-AF
Image Sensor	1/3" GC4653 4MP CMOS Sensor
Resulation	4MP 2560 x 1440
Video Compression Standard	H.264/H.265/H.265+
Dual Lens	2.8 mm @ F1.6 + 12 mm @ F1.6
IR LED	6 IR LED
IR Distance	30 Meter
White LED	6 White LED
IR Distance	25 Meter
Video Compression Code Stream	Main Stream : 2560 x 1440@15fps Sub Stream : 800 x 448@15fps
Audio Input\ Output	Supports two-way audio, built-in microphone and speaker
PT	Pan 0 ° - 350 ° Tilt 0 ° - 90 ° Horizontal Speed 20 ° / S Vertical Speed 10 ° / S
Day & Night	IR-cut Auto ICR
Minimum Illumination	Color : 0.01Lux, black and white : 0.001 Lux
Audio Compression Standard	AAC/G711A
WDR	Support DWDR
Eelectronic Shutter	Auto
4G band	FDD-LTE:B1/B3/B5/B8; TDD-LTE:B34/B38/B39/B40/B41;
Ethernet Port	1xRJ45 Port 10-100M adaptive
Video Tuning	contrast, brightness, saturation, sharpness adjustment

Alarm	1. Motion Detection, Alarm picture push 2. Human Detection
Monitoring	Android & Iphone /Windows PC (Application Truecloud)
Storage	Support Micro SD card (Max256G)
Communication Protocol	N1 & Onvif Support
Power	DC 12V/1A
Power Consumption	≤15W
Working Temp	0~50°C RH Less than 95% (No condensation)
Storage Temperature/Humidity	-20°C to +60°C / 20% to 90% RH
Housing Type	IP66 Housing
Dimension	132x191x170 (LxWxH)
Weight Net	0.567Kg 0.782Kg

Similar Products



Smart 4G
Bullet Camera T18075



4G Solar Mini
PT Camera T18021



Robot Monitoring Camera
T18061



Smart Wi-Fi Camera with
Battery Backup T18058



4G Dome Camera
T18021

* Note: Product specifications are subject to change without prior notice.