



ACE Pro Green Linkage Solar Powered Camera

3+3 MP

KEY FEATURES

- 3MP + 3MP 4G Solar Linkage PT Camera
- 4mm + 4mm Fixed Lens
- Horizontal Movement Range Pan 266° & Vertical Movement Range Tilt 90°
- Dual monitoring. One camera for monitoring, One camera for Pan-Tilt monitoring
- Built-in high-sensitivity Mic and Speaker, for Full Duplex Audio Intercomm
- Mobile Notification on Human & Motion Detection
- Support 10X Digital Zoom
- Can set 6 preset points favorite locations
- Built-in PIR Sensor, Active defense Siren & Lights
- Customized Voice Recordable message for Audio Alerts Boardcast
- Support Micro SD Card upto 256GB
- Night Vision and Full Color Modes
- Godrej ACE mobile app/ PC Software
- 4G Connection, QR code camera configuration with mobile/PC
- Built-in Battery 18000 mAh rechargeable lithium battery with 7 Watt Solar Panel

Camera

Image Sensor	1/2.8" 3MP+3MP HD CMOS Dual Sensor
Resolution	3MP + 3MP (2304 x 2592)
Lens	4mm + 4mm fixed lens
IR LED	Fixed Camera 4 Array, PT Camera 4 Array
IR Distance	30 Meters
White LED	Fixed Camera 4 White, PT Camera 4 White
White LED Distance	20 Meters
Video Compression Standard	H.264/H.265
Video Streaming	Main Stream: 2304 x 2592 / 15 fps, Sub Stream: 800 x 896 /15 fps
Audio Input/Output	Two way audio, Built in microphone and speaker
Audio Compression Standard	AAC/G711A
AI Features	Human Detection, Motion Detection, Human Tracking
PIR Sensor	10 Meters distance, 120 degrees cover
Slots	Nano Sim Card Slot & Micro SD Card Slot
Min Illumination	Color: 0.01 Lux, Black & White: 0.001 Lux
DNR	3D Digital Noise Reduction
White Balance	Auto
WDR	D-WDR
Mirror/Flip	On / Off
Electronic Shutter	Auto
Monitoring	Android, iOS, Windows
Storage	Support Micro SD Card upto 256GB
Connection Mode	4G Network
Light Mode	LED Flash; 4G Network not Connected. LED Continue ON; 4G Network Connected
Button	Reset Button
Battery	Built-in 18000mAh Rechargeable battery
Solar Panel	7 Watts
Power Input	DC: 5V/2A (Type-C)
Power Consumption	≤ 15W
Thunder Prevention	Standard IEC61000-4-5
Working Temperature / Humidity	-10° C to 50° C / 30% to 80% RH
Storage Temperature / Humidity	-20° C to 60° C / 20% to 90% RH
Housing Type	Plastic (IP66) Housing
Dimension	155(W)*210(H)*185(L)mm
Net Weight	900 Gms
Gross Weight	1000 Gms