SECURITY	
Network Security	SPI Firewall Access Control
	HomeShield Security
	Real-Time IoT Protection
	Malicious Site Blocker Intrusion Prevention System
	DDoS Attack Prevention
	Home Network Scanner
Guest Network	1× 5 GHz Guest Network
	1× 2.4 GHz Guest Network
Wi-Fi Security	WPA/WPA2/WPA3
WIRELESS	
Standards	Wi-Fi 6
	IEEE 802.11ax/ac/n/a 5 GHz IEEE 802.11ax/n/b/g 2.4 GHz
	AX3000
WiFi Speeds	5 GHz: 2402 Mbps (802.11ax)
	2.4 GHz: 574Mbps (802.11ax)
	1-3 Bedroom Houses (1-pack)
	TP-Link Mesh Technology
	Optional Ethernet backhaul work together to link Deco units to provide seamless coverage
WiFi Range	Al-Driven Mesh
	Intelligently learns the network environment to provide ideal Wi-Fi
	unique to your home
	2× Antennas (Internal)
	Multiple antennas form a signal-boosting array to cover more
	directions and large areas
WiFi Capacity	High Dual Bond
	Dual-Band  Distribute devices to different bands for optimal performance
	MU-MIMO
	Simultaneously communicates with multiple MU-MIMO clients

## **WIRELESS**

	OFDMA
	Simultaneously communicates with multiple WiFi 6 clients
	4 Streams
	More than enough bandwidth for connected devices
Working Modes	Router, Access Point
HARDWARE	
	2 × Gigabit ports per Deco unit
Ethernet Ports	(PoE and WAN/LAN auto-sensing)
Power	Power Input IEEE 802.3at PoE or 100-240V~50/60Hz 0.5A AC
	TEEE 802.341 POE 01 100-240V~50/60Hz 0.5A AC
SOFTWARE	
Protocols	IPv4
	IPv6
	IF VO
Service Kit	HomeShield
	<u>Learn More&gt;</u>
	HomeShield Parental Controls
Parental Controls	Youtube Restriction
	SafeSearch
	Custom Profiles
	Professional Content Filter Library
	Family Time
	Bedtime
	Bedtime Off Time
	Off Time Time Rewards
	Off Time Time Rewards Family Online Time Ranking
	Off Time Time Rewards
	Off Time Time Rewards Family Online Time Ranking Pause the Internet Weekly and Monthly Reports
	Off Time Time Rewards Family Online Time Ranking Pause the Internet Weekly and Monthly Reports  Dynamic IP
WAN Types	Off Time Time Rewards Family Online Time Ranking Pause the Internet Weekly and Monthly Reports  Dynamic IP Static IP
WAN Types	Off Time Time Rewards Family Online Time Ranking Pause the Internet Weekly and Monthly Reports  Dynamic IP Static IP PPPoE
WAN Types	Off Time Time Rewards Family Online Time Ranking Pause the Internet Weekly and Monthly Reports  Dynamic IP Static IP PPPoE L2TP
WAN Types	Off Time Time Rewards Family Online Time Ranking Pause the Internet Weekly and Monthly Reports  Dynamic IP Static IP PPPoE
WAN Types  Quality of Service	Off Time Time Rewards Family Online Time Ranking Pause the Internet Weekly and Monthly Reports  Dynamic IP Static IP PPPoE L2TP

## SOFTWARE

Cloud Service	OTA Firmware Upgrade TP-Link ID DDNS
NAT Forwarding	Port Forwarding UPnP
IPTV	IGMP Proxy IGMP Snooping Bridge Tag VLAN
DHCP	Address Reservation DHCP Client List Server
DDNS	TP-Link
Management	Deco App
TEST DATA	
WiFi Transmission Power	FCC: <30 dBm(2.4 GHz), <30 dBm(5 GHz) CE: <20 dBm (2.4 GHz), <30 dBm (5 GHz)
PHYSICAL	
Dimensions (W×D×H)	4.3 × 4.8 × 8.5 in (110 × 121.3 × 215.5 mm)
OTHERS	
Certification	CE, FCC, RoHS
Package Contents	1 × Deco X50-Outdoor unit 1 × AC Power Cord 1 × RJ45 Ethernet cable Wall/Pole Mounting Kit Installation Guide
Environment	Operating Temperature: -30°C~60°C (-22°F~140°F) Storage Temperature: -40°C~70°C (-40 °F~158 °F) Operating Humidity: 10%~90% RH Storage Humidity: 5%~90% RH

For additional version information, please go to the support page.