

4 Port POE Switch with 2 Uplink Port

ESCN04POE2U



4 Port POE Switch with 2 Uplink Port

ESCN04POE2U

Technical Specifications

Feature	Specifications
Product Code	ESCN04POE2U
Power Supply	Power Adaptor, 52V/1.5A
PoE Port	4×10/100 Mbps
Uplink Port	2×10/100 Mbps
Network Standard	IEEE802.3, IEEE802.3u, IEEE802.3X
PoE Standard	IEEE802.3af/at
Backplane Bandwidth	1.2Gbps
Forwarding Capacity	0.86Mpps
Packet Buffer	768K
MAC Address List	2K
Forward Mode	Store-and- forward
	Default: All port can be communicated freely,link speed is 10/100Mbps
Mode Switch	Extend: Port 1-4, Speed 10Mbps, Maximum transmission distance up to 250 meters;Port 1-4 are isolated respectively, but can communicate with Port 5-6
PoE Power Mode	End-span 1/2(+),3/6(-)
PoE Power Budget	Each port ≤30W Whole device≤72W
	Surge Protection: 4KV (common mode),10/700us IEC61000-4-5
Protection	ESD Protection: Contact Discharge: ±4KV
	Air Discharge: ±6KV Standard: IEC61000-4-2
Operating Temperature	-20~55°C 5%-95% (non-condensing)
Storage Temperature	-40~75°C 5%-95% (non-condensing)
Mean time between failures (MTBF)	>50000h