

2MP AHD HA-DVR-2104-L

- H.265 dual-stream video compression
- Supports AHD/HQA/CVI/CVBS/IP video inputs
- Max 5 channels IP camera inputs, each channel up to 2MP; Max 20Mbps incoming bandwidth
- Long transmission distance over coax cable
- Supports 1 SATA HDD, up to 6TB



SYSTEM OVERVIEW

With the surveillance operators pursuing to HD/UHD which further adds the storage and transmission cost, H.265 has been released to incredibly decrease the required bitrate while ensuring the video quality in realizing high resolution surveillance such as 4MP/4K.

The Lite Series is designed for high cost performance and quality. The range offers a great solution for users facing budget constraints who both require quality and performance. And with the adoption of Smart H.265, the series improves encoding efficiency, saving on bandwidth/storage costs, and significantly reducing the Total Cost of Ownership (TCO).

FUNCTIONS

Smart H.265

Smart Codec, H.265 can reduce up to 90% bit rate and storage requirements compared with H.264 without having to invest in new cameras.

AHD/HQA/CVI/CVBS/IP Auto-detect

The DVR can auto recognize the signal of front-camera without any setting. It makes operation more friendly and convenient.

2MP Resolution

The DVR supports up to 2MP AHD camera and IPC input.

Coaxial Audio/Upgrade/Alarm

The integrated design can reduce wiring troubles which makes it much more cost-effective and convenient for installation.

Long Distance Transmission

The DVR system supports long distance transmission over coaxial cable and UTP, max. 700m for 4K/4MP, 800m for 1080P and 1200m for 720P.

Smart Search

This function helps you get more motion detect video during a short time through drawing a region when playback. It is very useful when an emergency occurs.

Perfect Image Quality

High performance chip provides perfect image quality with better color reproduction.

P2P

Monitor at anytime and anywhere. Easily and conveniently manage the device.

Technical Specification

System

| | |
|------------------|--------------------|
| Main Processor | Embedded Processor |
| Operating System | Embedded LINUX |

Video and Audio

| | |
|---------------------|-----------------------------|
| Analog Camera Input | 4 Channel, BNC |
| HD Camera | 1080P@25/30, 720P@25/30fps |
| CVBS Camera | PAL/NTSC |
| IP Camera Input | 4+1, each channel up to 2MP |
| Audio In/Out | 1/1, RCA |
| Two-way Talk | Reuse audio in/out, RCA |

Recording

| | |
|-------------------|--|
| Video Compression | H.265 / H.264 |
| Resolution | 1080N, 720P, 960H, D1, CIF |
| Record Rate | Main Stream: 1080N/720P/960H/D1/CIF (1~25/30fps) Sub stream:CIF (1~15fps) |
| Video Bit Rate | 32Kbps ~ 4096Kbps Per Channel |
| Record Mode | Manual, Schedule (General, Continuous), MD (Video detection: Motion Detection, Video Loss, Tampering), Alarm, Stop |
| Record Interval | 1 ~ 60 min (default: 60 min), Pre-record: 1 ~ 30 sec, Post-record: 10 ~ 300 sec |
| Audio Compression | AAC(only for the 1st channel), G.711A, G.711U, PCM |
| Audio Sample Rate | 8KHz, 16 bit Per Channel |
| Audio Bit Rate | 64Kbps Per Channel |

Display

| | |
|----------------------|--|
| Interface | 1 HDMI ,1 VGA |
| Resolution | 1920×1080, 1280×1024, 1280×720 |
| Multi-screen Display | When IP extension mode not enabled : 1/4 When IP extension mode enabled : 1/4/6 |
| OSD | Camera title, Time, Video loss, Camera lock, Motion detection, Recording |

Network

| | |
|------------------|---|
| Interface | 1 RJ-45 Port (100M) |
| Network Function | HTTP, HTTPS, TCP/IP, IPv4/IPv6, 3G/4G, UPnP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPoE, DDNS, FTP |
| Max. User Access | 128 users |
| Smart Phone | iPhone, iPad, Android |
| Interoperability | ONVIF Conformant |

Video Detection and Alarm

| | |
|----------------|--|
| Trigger Events | Recording, PTZ, Tour, Video Push, Email, FTP, Snapshot, Buzzer and Screen Tips |
| Alarm input | N/A |
| Relay Output | N/A |

Playback and Backup

| | |
|-------------------|---|
| Playback | 1/4 |
| Search Mode | Time /Date, Alarm, MD and Exact Search (accurate to second) |
| Playback Function | Play, Pause, Stop, Rewind, Fast play, Slow Play, Next File, Previous File, Next Camera, Previous Camera, Full Screen, Repeat, Shuffle, Backup Selection, Digital Zoom |
| Backup Mode | USB Device/Network |

Storage

| | |
|--------------|---------------------------------|
| Internal HDD | 1 SATA Port, up to 6TB capacity |
|--------------|---------------------------------|

Auxiliary Interface

| | |
|-------|-------------------------|
| USB | 2 USB 2.0 |
| RS485 | 1 Port, for PTZ Control |

Electrical

| | |
|---------------------------------|------------|
| Power Supply | DC12V/1.5A |
| Power Consumption (without HDD) | <10W |

Construction

| | |
|--------------------------|-------------------------------|
| Dimensions | 260×236×48mm(10.2"×9.3"×1.9") |
| Net Weight (without HDD) | 0.9kg (2.0lb) |
| Gross Weight | 1.6kg (3.5lb) |
| Installation | Desktop installation |

Environmental

| | |
|----------------------|--|
| Operating Conditions | -10°C ~ +45°C (+14°F ~ +113°F), 10~ 90% RH |
| Storage Conditions | -20°C ~ +70°C (-4°F ~ +158°F) , 0~ 90% RH |




Certifications

| | |
|----------------|---------------|
| Certifications | BIS certified |
|----------------|---------------|


Ordering Information

| Type | Part Number | Description |
|------|---------------|-----------------------------|
| DVR | HA-DVR-2104-L | 4ch, 2MP DVR, 1 SATA, H.265 |

Dimensions (mm)



Rear Panel



| | | | |
|---|--------------------------|---|--------------------|
| 1 | VIDEO IN | 6 | RS485 Interface |
| 2 | AUDIO IN, RCA Connector | 7 | USB Interface |
| 3 | AUDIO OUT, RCA Connector | 8 | DC 12V Power Input |
| 4 | HDMI Interface | 9 | VGA Interface |
| 5 | Network Interface | | |

For more information,

www.partnerconnect.honeywell.com

Call: 1-800-103-0339

Email: HoneywellSecurity&Fire@honeywell.com

Honeywell HBT India Buildings

Unitech Trade Center, 5th Floor, Sector-43,
Block C, Sushant Lok Phase - I,
Gurgaon - 122 002

www.honeywell.com

© 2019 Honeywell International Inc.

2MP AHD
HA-DVR-2104-L

Honeywell