



Main

Range	EasyPact
Product or component type	Circuit breaker
Device short name	CVS400F
Device application	Distribution

Complementary

Poles description	3P
Protected poles description	3D
Network type	AC
Network frequency	50/60 Hz
Control type	Toggle
Mounting mode	Fixed
Mounting support	Backplate
Upside connection	Front
Downside connection	Front
[In] rated current	400 A at 40 °C
[Ui] rated insulation voltage	690 V AC 50/60 Hz conforming to EN/IEC 60947-2
[Uimp] rated impulse withstand voltage	8 kV conforming to EN/IEC 60947-2
[Ue] rated operational voltage	440 V AC 50/60 Hz conforming to EN/IEC 60947-2
Breaking capacity code	F
Breaking capacity	40 KA Icu at 220/240 V AC 50/60 Hz conforming to IEC 60947-2 36 KA Icu at 380/415 V AC 50/60 Hz conforming to IEC 60947-2 30 KA Icu at 440 V AC 50/60 Hz conforming to IEC 60947-2
[Ics] rated service breaking capacity	40 KA at 220/240 V AC 50/60 Hz conforming to IEC 60947-2 36 KA at 380/415 V AC 50/60 Hz conforming to IEC 60947-2 23 KA at 440 V AC 50/60 Hz conforming to IEC 60947-2
Suitability for isolation	Yes conforming to EN/IEC 60947-2
Utilisation category	Category A
Mechanical durability	15000 cycles
Electrical durability	6000 Cycles 415 V In conforming to IEC 60947-2 12000 cycles 415 V In/2 conforming to IEC 60947-2
Connection pitch	45 mm
Trip unit name	ETS 6.3
Trip unit technology	Electronic
Trip unit protection functions	LSIG
Trip unit rating	400 A at 40 °C
Protection type	Short time short-circuit protection Overload protection (long time) Ground fault protection Instantaneous short-circuit protection
Long time pick-up adjustment type Ir	Adjustable
Long time pick-up adjustment range	160...400 A

Long time delay adjustment type	Adjustable
[tr] long-time delay adjustment range	15...400 S at 1.5 x Ir 0.35...11 S at 7.2 x Ir 0.5...16 s at 6 x Ir
Thermal memory	20 minutes before and after tripping
Short-time pick-up adjustment type Isd	Adjustable
[Isd] short-time pick-up adjustment range	1.5...10 x Ir
Short-time delay adjustment type	Adjustable
[tsd] short-time delay pick-up	0...0.4 s
Instantaneous pick-up adjustment type li	Adjustable
Instantaneous pick-up	1.5...12 x In Easypact CVS400
Ground-fault pick-up adjustment type	Adjustable
Ground-fault time delay adjustment type -tg	Adjustable
[tg] ground-fault time delay adjustment range	0...0.4 s
[Ig] ground-fault pick-up adjustment range	80...400 A
Zone selective interlocking ZSI	Without
Display type	LCD display
Electrical shock protection class	Class II
Electrical data recording	Maintenance indicators
Height	255 mm
Width	140 mm
Depth	110 mm

Environment

Standards	IEC 60947-2 EN 60947-2
Product certifications	CB
IP degree of protection	IP40 conforming to IEC 60529
IK degree of protection	IK07 conforming to IEC 62262
Pollution degree	3 conforming to IEC 60664-1
Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-50...85 °C
Net weight	2.05 kg

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	18.0 cm
Package 1 Width	36.0 cm
Package 1 Length	29.0 cm
Package 1 Weight	8.6 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant  EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	 End Of Life Information
PVC free	Yes