

CM-2090

Features:

- SMART AC Digital Flexible Clamp.
- Ø 75mm.
- 6,000 Counts.

DC VOLTAGE

Range	Resolution	Accuracy
6V	0.001V	±0.8% of rdg + 3 digits
60V	0.01V	
600V	0.1V	

AC VOLTAGE

Range	Resolution	Accuracy	
		45 - 65Hz	40 - 2000Hz
6V	0.001V	± 1.2% of rdg + 3 digits	± 2.0% of rdg + 5 digits
60V	0.01V		
600V	0.1V		

FREQUENCY

Range	Resolution	Accuracy
40 - 1000Hz	0.1Hz	±0.5% of rdg + 2 digits
1kHz - 10KHz	1Hz	

AC CURRENT

Range	Resolution	Accuracy		
		40 - 65Hz	65 - 400Hz	400-1, 000Hz
60A	0.01A	± 3.0% of rdg + 5 digits	± 3.0% of rdg + 5 digits	-
600A	0.1A			
3000A	1A			

- Standard Accessories : Soft Carrying Case, Test Lead, Manual
- Dimension : 324(H) x 178(W) x 30(D)mm



RESISTANCE

Range	Resolution	Accuracy
6kΩ	0.001kΩ	±1.0% of rdg + 3 digits
60kΩ	0.01kΩ	
600kΩ	0.1kΩ	
6MΩ	0.001MΩ	
POWER	AAA 1.5V X 3	

CL-2054



Features:

- 10uA high Resolution
- Large 3 ¾ (4000 counts) LCD Display
- Auto Power OFF (APO)
- Shielded transformer jaw opens to 1.2"

AC VOLTAGE

Range	Resolution	Accuracy	
		50/60 Hz	40-1KHz
400V	0.1V	± 1.5% of rdg ± 2 digits	± 2.0% of rdg ± 4 digits

AC CURRENT

Range	Resolution	Accuracy	
		50/60 Hz	Wide (400-1KHz)
40mA	10µA	± 1.0% of rdg ± 0.5mA digits	± 4.5% of rdg ± 0.5mA digits
400mA	100µA	± 3.0% of rdg ± 5.0mA digits	± 3.0% of rdg ± 5.0mA digits
4A	1mA	± 4.0% of rdg ± 0.1A digits	± 4.0% of rdg ± 0.1A digits
40A	10mA	± 4.0% of rdg ± 1.0A digits	± 4.0% of rdg ± 1.0A digits
80A	100mA	± 2.5% of rdg ± 1.0A digits	± 3.0% of rdg ± 1.5A digits
80-100A		± 5.0% of rdg ± 1.0A digits	± 5.0% of rdg ± 1.5A digits

RESISTANCE

Range	Resolution	Accuracy
40-400Ω	0.1Ω	± 1.0% of rdg ± 2 digits

CONTINUITY TEST

Threshold 40Ω, Continuity Beeper 2.5KHz

POWER

9V (6F22) X 1

- Standard Accessories : Hard Carrying Case, Test Lead, Manual
- Dimension : 209(H) x 43(W) x 30(D)mm