

MINI-58C

1.5 HP MINI SERIES PUMP



Gardens & fountains



Feed water to RO plants



Domestic water supply



Construction sites



Overhead tanks in bungalows



Car washing

MONTHS WARRANTY



Lawn sprinklers







CED Coating

Provides superior resistance against corrosion



Thermal
Overload Protector (TOP)

Prevents the motor from burning due to overloading



Wide Voltage Range Operability

Protects the motor from burning due to lower/higher voltage



Enhanced Safety Features

Covered electrical parts offer additional safety



aı



logos on packaging



MINI-58C

1.5 HP MINI SERIES PUMP

Applications

- > Gardens and fountains
- Domestic water supply
- Construction sites
- > Feed water to RO plants
- Water supply to overhead tanks in bungalows
- Car washing

Lawn sprinklers

Features

- High Efficiency and Energy Saving Design: Innovative design manufactured at state of art plant, delivers optimum efficiency at lower energy consumption resulting in significant cost savings.
- Cathodic Electro Deposition (CED) Coating: CED is the latest coating technology for corrosion resistance with uniform coating, provides 5 times more protection over conventional painting, resulting in longer life. Hydraulic parts of Kirloskar pumps are CED coated.
- High Grade F Class Insulation: Robust design to withstand higher temperatures reducing the chances of motor burning and ensures the reliability, safety and enhanced life.
- Thermal Overload Protector (TOP): The pump set features a Thermal Overload protector that protects the motor from overloading, shielding the motor and associated circuit from the effects of fault current.
- Wide Voltage Range: The motor is designed to withstand wide voltage variation from 180 to 240 volts and reduces chances of motor burning due to low/high voltage.
- Shielded Ball Bearing: The pumps are fitted with shielded ball bearings, which results in low noise level and so no external lubrication is required throughout the life cycle.
- Dynamically Balanced Rotating Parts: Minimum vibrations protect components from damages during the operations, consistent performance as concentricity is maintained.
- ➤ Easy Maintainable Designs: Easy maintainable design and better interchangeability of components so that pump can be serviced even at remote locations by semi-skilled technicians.
- ➤ **High Suction Lift:** The pump has suction lift capacity up to 7.5 meters with high head, allowing to pump water at high volumes for a variety of applications.
- Enhanced Safety Features: All electrical parts of the pump are covered, which makes it safer to use.
- ➤ Light weight and Compact Design: It allows user to carry the pump anywhere with ease, adding to its portability and convenience of use.

Technical Specifications

Model	Mini-58C (Gold)
Head Range	Upto 58 M
Capacity Range	Upto 4800 LPH
Power Rating	1.1 kW/1.5 HP
Phase	Single
Voltage Range	180-240 (Volts)
Insulation	'F' Class
Protection	IP44

Material of Construction

Impeller	Brass
Delivery Casing	Cast Iron
Motor Body	Aluminium
Shaft	Carbon Steel
Cover NDE	Cast Iron
Mechanical Seal	Carbon Vs. Ceramic

PERFORMANCE CHART FOR MINI 58C MINI RANGE PUMP, 2 POLE, AT RATED VOLTAGE, 50 Hz FREQUENCY, SINGLE PHASE A.C. POWER SUPPLY

Pump Model	Power Rating		Pipe Size (mm)		Rated Voltage	Total Head in Meters																		
						10	12	14	18	20	22	24	26	28	30	32	34	38	40	42	50	52	54	58
	kW	HP	Suc.	Del.	(Volts)	Discharge in LPH																		
Mini-58C (Gold)	1.1	1.5	25	25	210	4800	4680	4530	4245	4100	3960	3815	3670	3490	3345	3165	3025	2700	2520	2375	1690	1510	1330	970

Note: Performance under standard test conditions. Performance applicable to liquid of specific gravity 1 and viscosity as of water.

KIRLOSKAR BROTHERS LIMITED

Established 1888

A Kirloskar Group Company

Registered Office & Global Headquarters: "Yamuna", Survey No. 98/(3 to7), Plot No. 3, Baner, Pune - 411 045, Maharashtra, India Tel: +91(20)27214444, Email: marketing@kbl.co.in, Website: www.kirloskarpumps.com

CIN No.: L29113PN1920PLC000670

