



N-Uface 602







Finger



RFID



(Optional)



WiFi



GPRS



Access

Multi-Bio Attendance and Access Control System

Storage Capacity

Face Capacity	3000
Finger Capacity	10,000
Card Capacity	10,000
Max User	10,000
Log Capacity	2,00,000

Features

World-class Face Identification Technology

High-Speed and Accurate Fingerprint Identification

Face, Fingerprint, Card, Passward authentication

1 output relay for door open.

Good adaptation for dry, moist and rough fingerprints.

Not necessary of bright lights during scans.

supremely low Electric energy consumption.

Comprehensive SDK is available for development & integration.



Communication Interface

Communication	WIFI, TCP/IP, RS232/485, USB
---------------	------------------------------

Biometric

Push Data	YES
4G GPRS	Optional
GPS	Optional
Sensor type	500 DPI
FAR	0.01%
FRR	0.001%
Processor	1 GHz High Speed CPU
OS	Linux
Verification time	<=1 second
RF card options	125kHz EM (Standard) /
	13.56MHz Mifare (Optional)



1 meter

Accepts Color Finger

Long Distance Verification

low light Verification

Auto Focus

Audio/Visual

LCD	4.3" touch screen 480x272 pixel
Voice instruction	16-bit Hi-Fi voice & sound indication
Language	English



Access control

Wiegand in & out	YES
Relay	YES
Support	RS485 Reader, Wiegand Reader,
	Remote, Push Button, No Touch



Time Attendance



Access Control



Employee Self Service



Mobile App

Power & Environment

Battery	Yes (Optional)
Operating Temperature	0°c ~ 50°c
Power	12V DC / 2A
Dimension (L*H*W)	195 x 150 x 100 mm

Disclaimer: Brief specifications are mentioned here. specification may change without prior notice. Customers are advised to check with us before purchase. Actual product may differ slightly to that depicted for ongoing product development.

BiomaxOfficial



Connect with us on



