



## N-X10

## Access Control System

---

### Capacity

RFID card capacity	100
Open door password capacity	5 (support virtual password)
The number of open passwords	4 digits (eg: 1234)
Programming password	6 digits
Card reading distance	1-5cm

### Power & Environment

Operating voltage	DC 12V
Locking relay	DC 12V / 2A
Working temperature	0° C ~ 45° C
Storage temperature	-20° C ~ 60
Relative humidity (Working)	40% to 90% RH
Relative humidity (Storage)	20% to 90% RH

# N-X10 Access Control System

## Function

Password identification
card recognition
wired doorbell control
Wiegand output
access control, switch control



## Access Control

Card Type	Em Card or Em Compatible Card (ID)
Programming password	123456 (default)
Open door mode	Card or digital password
Lock relay time	Can set (00~99)S
Tamper alarm	OPEN
Open card function	Yes
Mother card function	Yes
Doorbell	wired doorbell

## Indicator light

Open the door, the green light is on
Enter the programming mode, the green light is always on
Standby state, no light
The card is not registered, when punch by card, the light turn red.
The door open password is wrong, the red light is on.

**Disclaimer :** Brief specifications are mentioned here. specification may change without prior notice. Customers are advised to check with us before purchase. Actual product may differ slightly to that depicted for ongoing product development.

### Connect with us on

-  BiomaxOfficial
-  BioMax Security
-  biomaxsecurity
-  BioMax Access Control

Certified by



[www.biomaxsecurity.com](http://www.biomaxsecurity.com)