Product datasheet

Specifications





AvatarOn, switched socket, 3P, 6 A, 250 V, Wine Gold

E8315_6_WG

Main

| Range | AvatarOn |
|----------------------------|------------------------------------|
| Product or component type | Switched socket |
| Device application | Power supply |
| device presentation | Complete product |
| Outlet poles configuration | 3P with shutter 2P with shutter |
| Colour tint | Wine gold |
| Type of packing | Flow-pack |
| Main colour tint | Wine gold |

Complementary

| Rated current | 6 A socket-outlet |
|--------------------------------|--|
| [Ue] rated operational voltage | 250 V AC 50/60 Hz |
| Socket number | 1 |
| Outlet standard description | With earthing contact |
| Outlet standard deviation | British BS 546 |
| Number of gangs | 1 gang |
| Service life in cycles | 20000 cycles |
| Electrical durability | 5000 cycles |
| Connections - terminals | Screw terminal |
| Material | Polycarbonate: grid plate Polycarbonate: surround |
| Surface finish | Glossy |
| Surface treatment | Painted cover plate |
| Device mounting | Surface |
| Fixing mode | Screw |
| Height | 86 mm |
| Width | 86 mm |
| Depth | 32.6 mm |

Environment

IP degree of protection IP20

| Ambient air temperature for operation | -545 °C | |
|---------------------------------------|---------|--|
| ambient air temperature for storage | -560 °C | |
| Standards | BS 546 | |
| | SS 472 | |
| | MS 1577 | |
| Product certifications | SIRIM | |

Packing Units

| • | |
|------------------------------|---------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 3.81 cm |
| Package 1 Width | 8.89 cm |
| Package 1 Length | 8.89 cm |
| Package 1 Weight | 91 g |
| Unit Type of Package 2 | BB1 |
| Number of Units in Package 2 | 8 |
| Package 2 Height | 9.5 cm |
| Package 2 Width | 19 cm |
| Package 2 Length | 19.5 cm |
| Package 2 Weight | 778 g |
| Unit Type of Package 3 | CAR |
| Number of Units in Package 3 | 48 |
| Package 3 Height | 210 cm |
| Package 3 Width | 299 cm |
| Package 3 Length | 395 cm |
| Package 3 Weight | 4.87 kg |
| | |



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

✓ Reach Free Of Svhc
 ✓ Mercury Free
 ✓ Rohs Exemption Information

Certifications & Standards

| Reach Regulation | REACh Declaration |
|--------------------------|---|
| Eu Rohs Directive | Compliant with Exemptions |
| China Rohs Regulation | China RoHS declaration Product out of China RoHS scope. Substance declaration for your information |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | No need of specific recycling operations |