

XUGA

X05B



XUGA

X05B



**5MP
ULTRA HD**



XUGA X05B

**YOUR MONITORING
ASSITANT**





XUGA

X05B

ALARM INFORMATION PUSHED TO CELL PHONE

The alert is sent to the phone at the first time,
you can know the details at home in 24 hours.



XUGA

X05B

SHARE WITH OTHERS INTIMATE FAMILY INTERACTION

Supports device sharing, allowing family members to synchronize to view the shooting screen or use more functions to share a better life.



Technical specifications

Model	Xuga X05B
Operating system	Linux
Online visitor	Supports 4 visitors viewing at the same time.
APP	O-KAM Pro
CPU	T23
Image sensor	GC2083, 1/3 CMOS
Minimum illumination	0.8Lux/F1.4(Color mode),0.3Lux/F1.4 (B&W mode)
Lens	Standard lens 14mm, 1G3P, focal length 4mm IR-CUT integrated
Viewing angle	Diagonal 100 °
Night Vision	Color night vision, dual light sources, visible distance: 10~20 meters
Data rate	Main stream: 1296P/15fps, sub stream: 360P/15fps
Bit rate	CBR/VBR two rate control modes, with an output rate range of 128 to 4096kbps.
Image adjustment	Brightness, contrast, vertical, horizontal adjustable, OSD display.
Input	Built-in-38dB microphone
Output	Built-in 8Ω1W speaker
Sampling frequency/bit width	8KHz/16bit
Humanoid detection	Humanoid detection, filtering invalid alarm events.
Human tracking	When it detects human figure, it will frame and track
Area detection	Only monitor areas that matter.
Intelligent notification sound	Set different notification sounds for different devices, so that you can accurately determine which device is triggered.
Intelligent alarm sound	Set different alarm sounds based on different scenarios.
More AI functions	Pets, vehicles, packages, etc
Network protocol	TCP/IP,HTTP,UDP,DHCP,DNS,NTP,RTSP,P2P,IPV4,IPV6 third party access protocols, etc
Wireless network	IEEE802.11b/g/n
Wireless security encryption	64/128-bit WEP/WPA-PSK/WPA2-PSK data encryption
Wireless connection method	AP hotspot, Scan QR code, Bluetooth
Reset key	Long press to restore factory settings
Indicator light	Dual color indicator lights together with voice prompt
Micro SD card	Supports Micro SD card (up to 256GB)
Alarm detection	Motion detection alarm, humanoid detection alarm
Rated voltage	DC5V, 1.5A
Power supply	TYP-C 5V/1.5A power supply
Operating condition	Temperature: -10 ~ 55°C; Humidity: < 90%
Packaging list	Camera*1, TYP-C*1, manual*1, 5V1.5A-TYP-C adapter